GP5000



GP SERIES

Commercial/Residential Portable Generators

A/C Rated Output Watts 5,000 A/C Maximum Output Watts 6,250

Model 5688-1

UPC Number: 696471056884

Emissions Certification: CSA Certified

Not for sale in California



features

- OHV SPLASH LUBRICATION
- HIGH PERFORMANCE ALTERNATOR
- STEEL FUEL TANK WITH FUEL GAUGE
- LOCKING FOLD-DOWN HANDLES
- NEVER-FLAT WHEEL KIT
- 1.25" HARDENED STEEL TUBE CRADLE
- HOUR METER WITH MAINTENANCE RESETS
- CIRCUIT BREAKER PROTECTED OUTLETS
- LOW TONE MUFFLER

customer connections

Receptacles


Α	(4) 5-20R 120V
В	L14-30R Twist-Lock 120/240V

Circuit Breakers

M	(2) 20A
N	(2) 25A

Other Features

H Hour Meter with Maintenance Reset



GP5000

specifications

GP5000
5688-1
CSA
5000
6250
120/240VAC
60 Hz
20.8
26.0
389cc
OHV
3600
5W30
Splash Sump
Manual Lever
Manual Lever
Full Speed
Manual
n/a
n/a
Low Level

Start Switch Type	3-Position
Switch Location	On Engine
Single-Point Lifting Eye	N/A
Fuel Gauge	Built-In
Fuel Tank Capacity (Gal)	6.6
Fuel Tank Capacity (Liters)	24.98
Run Time at 50% (Hours)	10
Cord Set	No
Handle Style	Folding Interlocked
Wheel type	9.5" Solid Wheels
Maintenance Kit	Sold Separately
Warranty - Residential	2 Year
Warranty - Commercial	1 Year

dimensions and weights

Length (L)	33.5
Width (W)	26.5
Height (H)	27.5
Extended Length (EL)	47
Carton Length	35.5
Carton Width	26.5
Carton Height	27.5
Unit Weight (lbs)	167
Shipping Weight (lbs)	180

