

GP7000

GP SERIES Commercial/Residential Portable Generators

1 of 2

A/C Rated Output Watts 7000
A/C Maximum Output Watts 8750

Model 5693-0

UPC Number: 696471056938

Emissions Certification: CSA Certified.

Not for sale in California.



features

- GENERAC OHVI OVERHEAD VALVE INDUSTRIAL ENGINE WITH FULL PRESSURE LUBRICATION AND SPIN-ON FILTER
- HIGH PERFORMANCE ALTERNATOR
- STEEL FUEL TANK WITH FUEL GAUGE
- LOCKING FOLD-DOWN HANDLES
- NEVER-FLAT WHEEL KIT
- 1.25" HARDENED STEEL TUBE CRADLE
- CIRCUIT BREAKER PROTECTED OUTLETS
- LOW TONE MUFFLER

customer connections

Outlets


A	(4) 5-20R 120V
B	L14-30R Twist-Lock 120/240V

Circuit Breakers

M	(2) 20A
N	(2) 30A

Other Features

H	Hour Meter with Maintenance Reset
----------	-----------------------------------



GP7000

specifications

Product Series	GP7000
Model	5693-0
Configuration/Emissions	49-State
A/C Rated Output Watts:	7000
A/C Maximum Output Watts:	8750
A/C Voltage	120/240VAC
A/C Frequency	60 Hz
Rated 120/240 VAC Amperage	29.2
Max 120/240 VAC Amperage	36.5
Engine Displacement	410cc
Engine Type	OHVI
Engine RPM	3600
Recommended Oil	5W30
Lubrication Method	Full Pressure
Choke Type	Manual Lever
Fuel Shut Off	Manual Lever
Idle Control	Full Speed
Starting Method	Manual
Battery	n/a
Battery Size	n/a
Low Oil Shutdown Method	Low Pressure

Start Switch Type	3-Position
Switch Location	On Engine
Single-Point Lifting Eye	N/A
Fuel Gauge	Built-In
Fuel Tank Capacity (Gal)	8
Fuel Tank Capacity (Liters)	30.28
Run Time at 50% (Hours)	11
Cord Set	No
Handle Style	Folding Interlocked
Wheel type	9.5" Solid Wheels
Maintenance Kit	Sold Separately
Warranty - Residential	2 Year
Warranty - Commercial	1 Year

dimensions and weights

Length (L)	33.5
Width (W)	26.5
Height (H)	27.5
Extended Length (EL)	47
Carton Length	35.5
Carton Width	26.5
Carton Height	27.5
Unit Weight (lbs)	177
Shipping Weight (lbs)	190

